



AMENTA Pigs

Robust lighting for pig houses.



5 YEARS
warranty



Benefits

- Perfect retrofit for existing installations.
- Optimised for price sensitive applications.
- Robust design for extreme stable conditions.
- Simple mounting and operation.

Characteristics

IP 66

IK 03

Frequency
0-50/60Hz

Rated voltage
220-240V

NON-SELV

Mechanical characteristics

Profile	Extruded PMMA with UV protection Red end caps Bottom part opal
End caps	PMMA, ASA
Gasket	PWIS-free silicone
Gear tray	White lacquered steel plate
Cable entry	Cable gland
Fixing clips	Stainless steel
Suspension triangles	Stainless steel

Electrical characteristics

Connection	3 pole push
THD	< 10% full load
Power factor	> 0.95 full load
Flicker factor	< 1%

Functional characteristics


Lifetime	L80 50,000 hours at 25°
Guarantee	5 years
Fire protection	Flammability (UL94): HB Glow wire test (EN 60695-2-11): 650°

Compliance



Photometrical characteristics

SDCM	< 3
------	-----



AMENTA | Pigs

Description

FAMILY	LENGTH (mm)	LUMINOUS FLUX (lm)	CRI	LIGHT COLOUR (K)	DRIVER	PROFILE	THROUGH WIRING
> AMENTA	> 1.2: 1200 > 1.5: 1500	> 42: 4200	8: >80	> 30: 3000 > 40: 4000	> ET: non dimmable	> BPM: PMMA	> LV: Power lines

Special options under request

Operational data

Description	Order number	Luminous flux (lm)	Power (W)	Efficiency (lm/W)	Light colour (K)	CRI
AMENTA 1.2 42-840 ET BPM LV	10228111	4200	33	127	4000	>80
AMENTA 1.5 42-840 ET BPM LV	10228115	4200	35	120	4000	>80

Dimensions and logistics

Description	X	Xm	Y	Z					
	mm	mm	mm	mm	L x W x H mm	Pcs./Box	Box	Groupage Pcs./Euro pallet	Double pallet Pcs./Euro pallet
AMENTA 1.2...	1213	800	76	67	1330 x 85 x 75	1	1.9	171	108 + 108
AMENTA 1.5...	1493	1100	76	67	1610 x 85 x 75	1	2.3	171	108 + 108

Please check with our Back Office to confirm logistic data

Accessories

10103049	Suspension wire 2m hook and fastener, 1 unit ²
10149442	Theft protection (required for wall mounting), set for 1 luminaire
10207593	ZBWM wall mounting accessory (allows luminaire rotation), 2 pieces set
10256809	Fixing clips in stainless steel 316L, 2 units

² 2 units required per luminaire

